

# Relational Query Optimization

## Chapter 15

# Highlights of System R Optimizer

- ❖ **Impact:**
  - Most widely used currently; works well for < 10 joins.
- ❖ **Cost estimation:** Approximate art at best.
  - Statistics, maintained in system catalogs, used to estimate cost of operations and result sizes.
  - Considers combination of CPU and I/O costs.
- ❖ **Plan Space:** Too large, must be pruned.
  - Only the space of *left-deep plans* is considered.
    - Left-deep plans allow output of each operator to be *pipelined* into the next operator without storing it in a temporary relation.
  - Cartesian products avoided.

# Overview of Query Optimization

- ❖ **Plan:** *Tree of R.A. ops, with choice of alg for each op.*
  - Each operator typically implemented using a 'pull' interface: when an operator is 'pulled' for the next output tuples, it 'pulls' on its inputs and computes them.
- ❖ Two main issues:
  - For a given query, **what plans are considered?**
    - Algorithm to search plan space for cheapest (estimated) plan.
  - How is the **cost of a plan estimated?**
- ❖ **Ideally:** Want to find best plan. **Practically:** Avoid worst plans!
- ❖ We will study the System R approach.

# Schema for Examples

Sailors (*sid: integer, sname: string, rating: integer, age: real*)  
 Reserves (*sid: integer, bid: integer, day: dates, rname: string*)

- ❖ Similar to old schema; *rname* added for variations.
- ❖ Reserves:
  - Each tuple is 40 bytes long, 100 tuples per page, 1000 pages.
- ❖ Sailors:
  - Each tuple is 50 bytes long, 80 tuples per page, 500 pages.

# Query Blocks: Units of Optimization

- ❖ An SQL query is parsed into a collection of *query blocks*, and these are optimized one block at a time.
- ❖ Nested blocks are usually treated as calls to a subroutine, made once per outer tuple. (This is an oversimplification, but serves for now.)
- ❖ For each block, the plans considered are:
  - All available access methods, for each reln in FROM clause.
  - All *left-deep join trees* (i.e., all ways to join the relations one-at-a-time, with the inner reln in the FROM clause, considering all reln permutations and join methods.)

```
SELECT S.sname
FROM Sailors S
WHERE S.age IN
  (SELECT MAX (S2.age)
   FROM Sailors S2
   GROUP BY S2.rating)
```

Outer block    Nested block

# Relational Algebra Equivalences

- ❖ Allow us to choose different join orders and to 'push' selections and projections ahead of joins.
  - ❖ **Selections:**  $\sigma_{c_1 \wedge \dots \wedge c_n}(R) \equiv \sigma_{c_1}(\dots \sigma_{c_n}(R))$  (Cascade)  
 $\sigma_{c_1}(\sigma_{c_2}(R)) \equiv \sigma_{c_2}(\sigma_{c_1}(R))$  (Commute)
  - ❖ **Projections:**  $\pi_{a_1}(R) \equiv \pi_{a_1}(\dots (\pi_{a_n}(R)))$  (Cascade)
  - ❖ **Joins:**  $R \bowtie (S \bowtie T) \equiv (R \bowtie S) \bowtie T$  (Associative)  
 $(R \bowtie S) \equiv (S \bowtie R)$  (Commute)
- + Show that:  $R \bowtie (S \bowtie T) \equiv (T \bowtie R) \bowtie S$

## More Equivalences

- ❖ A projection commutes with a selection that only uses attributes retained by the projection.
- ❖ Selection between attributes of the two arguments of a cross-product converts cross-product to a join.
- ❖ **A selection on just attributes of R commutes with  $R \bowtie S$ . (i.e.,  $\sigma(R \bowtie S) \equiv \sigma(R) \bowtie S$ )**
- ❖ Similarly, if a projection follows a join  $R \bowtie S$ , we can 'push' it by retaining only attributes of R (and S) that are needed for the join or are kept by the projection.

## Enumeration of Alternative Plans

- ❖ There are two main cases:
  - **Single-relation plans**
  - **Multiple-relation plans**
- ❖ For queries over a single relation, queries consist of a combination of selects, projects, and aggregate ops:
  - Each available access path (file scan / index) is considered, and the one with the least estimated cost is chosen.
  - The different operations are essentially carried out together (e.g., if an index is used for a selection, projection is done for each retrieved tuple, and the resulting tuples are **pipelined** into the aggregate computation).

## Cost Estimation

- ❖ For each plan considered, must estimate cost:
  - Must **estimate cost** of each operation in plan tree.
    - Depends on input cardinalities.
    - We've already discussed how to estimate the cost of operations (sequential scan, index scan, joins, etc.)
  - Must also **estimate size of result** for each operation in tree!
    - Use information about the input relations.
    - For selections and joins, assume independence of predicates.

## Cost Estimates for Single-Relation Plans

- ❖ Index I on primary key matches selection:
    - Cost is  $Height(I)+1$  for a B+ tree, about 1.2 for hash index.
  - ❖ Clustered index I matching one or more selects:
    - $(NPages(I)+NPages(R))$  \* product of RF's of matching selects.
  - ❖ Non-clustered index I matching one or more selects:
    - $(NPages(I)+NTuples(R))$  \* product of RF's of matching selects.
  - ❖ Sequential scan of file:
    - $NPages(R)$ .
- + **Note:** Typically, **no duplicate elimination** on projections!  
(Exception: Done on answers if user says DISTINCT.)


## Example

```
SELECT S.sid
FROM Sailors S
WHERE S.rating=8
```

- ❖ If we have an **index on rating**:
  - $(1/NKeys(I)) * NTuples(R) = (1/10) * 40000$  tuples retrieved.
  - **Clustered index:**  $(1/NKeys(I)) * (NPages(I)+NPages(R)) = (1/10) * (50+500)$  pages are retrieved. (This is the **cost**.)
  - **Unclustered index:**  $(1/NKeys(I)) * (NPages(I)+NTuples(R)) = (1/10) * (50+40000)$  pages are retrieved.
- ❖ If we have an **index on sid**:
  - Would have to retrieve all tuples/pages. With a **clustered** index, the **cost** is 50+500, with **unclustered** index, 50+40000.
- ❖ Doing a **file scan**:
  - We retrieve all file pages (500).

## Queries Over Multiple Relations

- ❖ Fundamental decision in System R: **only left-deep join trees** are considered.
  - As the number of joins increases, the number of alternative plans grows rapidly; we need to restrict the search space.
  - Left-deep trees allow us to generate all **fully pipelined plans**.
    - Intermediate results not written to temporary files.
    - Not all left-deep trees are fully pipelined (e.g., SM join).



## Enumeration of Left-Deep Plans

- ❖ Left-deep plans differ only in the order of relations, the access method for each relation, and the join method for each join.
- ❖ Enumerated using N passes (if N relations joined):
  - **Pass 1:** Find best 1-relation plan for each relation.
  - **Pass 2:** Find best way to join result of each 1-relation plan (as outer) to another relation. (*All 2-relation plans.*)
  - **Pass N:** Find best way to join result of a (N-1)-relation plan (as outer) to the N'th relation. (*All N-relation plans.*)
- ❖ For each subset of relations, retain only:
  - Cheapest plan overall, plus
  - Cheapest plan for each *interesting order* of the tuples.

## Enumeration of Plans (Contd.)

- ❖ **ORDER BY, GROUP BY, aggregates** etc. handled as a final step, using either an 'interestingly ordered' plan or an additional sorting operator.
- ❖ An N-1 way plan is not combined with an additional relation unless there is a join condition between them, unless all predicates in WHERE have been used up.
  - i.e., **avoid Cartesian products if possible.**
- ❖ In spite of pruning plan space, this approach is **still exponential** in the # of tables.


## Cost Estimation for Multirelation Plans

```
SELECT attribute list
FROM relation list
WHERE term1 AND ... AND termk
```

- ❖ Consider a query block:
- ❖ Maximum # tuples in result is the product of the cardinalities of relations in the FROM clause.
- ❖ **Reduction factor (RF)** associated with each *term* reflects the impact of the *term* in reducing result size. **Result cardinality = Max # tuples \* product of all RF's.**
- ❖ **Multirelation plans are built up by joining one new relation at a time.**
  - Cost of join method, plus estimation of join cardinality gives us both cost estimate and result size estimate

## Example

```
Sailors:
B+ tree on rating
Hash on sid
Reserves:
B+ tree on bid
```



- ❖ **Pass 1:**
  - **Sailors:** B+ tree matches  $rating > 5$ , and is probably cheapest. However, if this selection is expected to retrieve a lot of tuples, and index is unclustered, file scan may be cheaper.
    - Still, B+ tree plan kept (because tuples are in *rating* order).
  - **Reserves:** B+ tree on *bid* matches  $bid=500$ ; cheapest.
- ❖ **Pass 2:**
  - We consider each plan retained from Pass 1 as the outer, and consider how to join it with the (only) other relation.
    - e.g., **Reserves as outer:** Hash index can be used to get Sailors tuples that satisfy *sid* = outer tuple's *sid* value.

## Nested Queries

```
SELECT S.sname
FROM Sailors S
WHERE EXISTS
(SELECT *
 FROM Reserves R
 WHERE R.bid=103
 AND R.sid=S.sid)
```

```
Nested block to optimize:
SELECT *
FROM Reserves R
WHERE R.bid=103
AND S.sid= outer value
```

```
Equivalent non-nested query:
SELECT S.sname
FROM Sailors S, Reserves R
WHERE S.sid=R.sid
AND R.bid=103
```

- ❖ Nested block is optimized independently, with the outer tuple considered as providing a selection condition.
- ❖ Outer block is optimized with the cost of 'calling' nested block computation taken into account.
- ❖ Implicit ordering of these blocks means that some good strategies are not considered. **The non-nested version of the query is typically optimized better.**

## Summary

- ❖ Query optimization is an important task in a relational DBMS.
- ❖ Must understand optimization in order to understand the performance impact of a given database design (relations, indexes) on a workload (set of queries).
- ❖ Two parts to optimizing a query:
  - Consider a set of alternative plans.
    - Must prune search space; typically, left-deep plans only.
  - Must estimate cost of each plan that is considered.
    - Must estimate size of result and cost for each plan node.
    - **Key issues:** Statistics, indexes, operator implementations.

## Summary (Contd.)

### ❖ Single-relation queries:

- All access paths considered, cheapest is chosen.
- *Issues*: Selections that *match* index, whether index key has all needed fields and/or provides tuples in a desired order.

### ❖ Multiple-relation queries:

- All single-relation plans are first enumerated.
  - Selections/projections considered as early as possible.
- Next, for each 1-relation plan, all ways of joining another relation (as inner) are considered.
- Next, for each 2-relation plan that is `retained`, all ways of joining another relation (as inner) are considered, etc.
- At each level, for each subset of relations, only best plan for each interesting order of tuples is `retained`.